



## Neste Marine 2T

2T oil for outboard engines

### PERFORMANCE CLAIMS

API TD

NMMA TC-W3

### DESCRIPTION

Neste Marine 2T is a two-stroke oil for outboard engines. It's based on a SAE 40 mineral base oil and contains 20% of solvent component to ensure blending. Ashless additives prevent wear, corrosion and deposit formation on pistons, combustion chambers and exhaust ports. Neste Marine 2T ensures the lubrication of fast moving parts in modern 2T outboard engines.

### FEATURES AND BENEFITS

- For injection and premix lubrication systems
- Ashless
- Low deposits

### TYPICAL CHARACTERISTICS

Density 15 °C	864	kg/m <sup>3</sup>	ASTM D4052
Flash Point (COC)	58	°C	ASTM D92
Pour Point	-42	°C	ASTM D5949
Sulfated Ash	1	w/w %	ASTM D874
Viscosity @ 100 °C	8,5	cSt	ASTM D445
Viscosity Index	142		ASTM D2270

### APPLICATIONS

Neste Marine 2T oil is particularly suitable for low mixture ratios used in high-power water-cooled outboard engines. It can also be used both in premix and oil injection lubrication. The oil is dyed green so that it is possible to see if the fuel blend contains oil. Synthetic Neste Super 2T and fully synthetic Neste Super Racing 2T are recommended for use in motorcycles, scooters, mopeds, chain saws and snowmobiles.