



Neste Hydraulic 22 Super

Super grade hydraulic oil

PERFORMANCE CLAIMS

ISO VG 22

ISO 11158 HV

DIN 51524-3 HVLP

DESCRIPTION

Neste Hydraulic 22 Super is top quality Super-class multigrade hydraulic oil for demanding outdoor use. It has an extremely wide operating temperature range and superb cold properties. Cold properties and high viscosity index enable best performance even in extremely cold conditions. Special additives developed for extreme conditions give effective protection against wear, oxidation and corrosion. Due to its good air release and demulsibility properties it can be used even in severe conditions.

FEATURES AND BENEFITS

- Extra wide operating temperature area
- Excellent anti_wear properties
- Effective protection against corrosion

TYPICAL CHARACTERISTICS

| | | | |
|--------------------|-----|-------------------|------------|
| Density 15 °C | 851 | kg/m ³ | ASTM D4052 |
| Flash Point (COC) | 202 | °C | ASTM D92 |
| Pour Point | -54 | °C | ASTM D5949 |
| Viscosity @ 100 °C | 5,1 | cSt | ASTM D445 |
| Viscosity @ -20 °C | 665 | cSt | ASTM D445 |
| Viscosity @ 40 °C | 22 | cSt | ASTM D445 |
| Viscosity Index | 168 | | ASTM D2270 |

APPLICATIONS

Neste Hydraulic 22 Super has excellent cold properties for winter time use. Neste Hydraulic Super oils are used, for example in excavators, forestry equipment, earth movers, fork lift trucks, cranes etc. hydraulics.