



## Neste Pro Axle 75W-140

Fully synthetic drive and differential gear oil

### PERFORMANCE CLAIMS

75W-140  
 API GL-5  
 Mack GO-J  
 MIL-PRF-2105E  
 SAE J2360  
 SCANIA STO 1:0  
 ZF TE-ML 05A, 16D, 19B

### DESCRIPTION

Neste Pro Axle 75W-140 is made of a fully synthetic base oil mixed with extreme pressure, oxidation and rust resistance additives. Good operation properties at severe below-zero temperatures and low friction drag, which make for good fuel economy, are special features of this oil.

### FEATURES AND BENEFITS

- Extra wide operating temperature area
- Excellent EP properties
- Low friction
- Good oxidation stability

### TYPICAL CHARACTERISTICS

Viscosity (CCS) @ -40 °C	111000		
Density 15 °C	855	kg/m <sup>3</sup>	ASTM D4052
Flash Point (COC)	220	°C	ASTM D92
Pour Point	-48	°C	ASTM D5949
Viscosity @ 100 °C	25	cSt	ASTM D445
Viscosity @ 40 °C	172	cSt	ASTM D445
Viscosity Index	181		ASTM D2270

### APPLICATIONS

Neste Pro Axle 75W-140 is for heavy-duty transportation - year-round use. It can be blended with ordinary gear oils if necessary and it does not damage the gaskets.

Neste Pro Axle 75W-140 fills Scania STO:1 requirements and is suitable for Scania drive gears especially in cold climate conditions.