



Neste Pro C3 5W-40

Fully Synthetic Motor Oil

PERFORMANCE CLAIMS

API SN, SM, SL, SJ/CF

ACEA C3

BMW Longlife-04 (-2019)

Ford WSS-M2C917

GM dexos2

MB 226.5

Porsche A40

APPROVALS

MB-Approval 229.31

Renault RN0700

Renault RN0710

VW 505 00 / 505 01

DESCRIPTION

Neste Pro C3 5W-40 is new age fully synthetic motor oil. Neste Pro C3 5W-40 is especially designed for highly developed modern engines with emission after treatment systems in both diesel and gasoline powered vehicles.

It exceeds new API SN and ACEA C3 performance requirements and many of car manufacturers' standards required for newer modern diesel and gasoline car engines such as BMW LL-04 and MB 229.31.

FEATURES AND BENEFITS

- Excellent cold start performance
- Fuel economy benefits
- Long drain interval
- Low emission

TYPICAL CHARACTERISTICS

Viscosity (CCS) @ -30 °C	6000		
Density 15 °C	854	kg/m ³	ASTM D4052
Flash Point (COC)	244	°C	ASTM D92
Pour Point	-51	°C	ASTM D5949
Base Number (TBN)	7.2	mg KOH/g	ASTM D2896
Viscosity @ 100 °C	14,2	cSt	ASTM D445
Viscosity @ 40 °C	87	cSt	ASTM D445
Viscosity Index	170		ASTM D2270

APPLICATIONS

Neste Pro C3 5W-40 is recommended for year-round use in gasoline and diesel engines of passenger cars and vans in all conditions.

Neste Pro C3 5W-40 exceeds the requirements of many car manufacturers' standards required for newer modern car engines but it is excellent oil also for older vehicles and for general use.