



Neste Farm Universal 10W-30

Super Tractor Oil Universal

PERFORMANCE CLAIMS

API CG-4, CF-4, CF, CE/SF

API GL-4

ACEA E3, E2, E1

Allison C-4, C-3

Caterpillar TO-2

Eaton Vickers I-286-S, M-2950-S

Ford WSS-M2C159B, C

JDM J20C

JDM J27

MF M1139, M1144, M1145

ZF TE-ML 06B, 06R, 07B

DESCRIPTION

Neste Farm Universal is a multigrade general-purpose oil for tractors and farm machinery. Its additives keep the engine clean and give efficient wear resistance in transmission, rear axles and hydraulics. Special friction modifiers make it suitable for lubricating wet brakes.

FEATURES AND BENEFITS

- Good cold start performance
- Broad coverage
- Wet brake compatible

TYPICAL CHARACTERISTICS

Viscosity (CCS) @ -25 °C	5500		
Density 15 °C	874	kg/m ³	ASTM D4052
Flash Point (COC)	224	°C	ASTM D92
Flash Point (PM)	198	°C	ASTM D93
Pour Point	-36	°C	ASTM D5949
Base Number (TBN)	10,4	mg KOH/g	ASTM D2896
Viscosity @ 100 °C	10,5	cSt	ASTM D445
Viscosity @ 40 °C	69	cSt	ASTM D445
Viscosity Index	140		ASTM D2270

APPLICATIONS

Neste Farm Universal is recommended for year-round use in most farm tractors as an engine, rear axle and hydraulic oil. It is suitable for both turbocharged and normally aspirated diesel engines. It can also be used in combined harvesters, stationary engines, passenger cars and vans, and truck and loading machinery.