



Neste Super Racing 2T

Fully synthetic 2T oil

PERFORMANCE CLAIMS

API TC++

JASO FD

ISO-L-EGD

Husqvarna 266

Piaggio Hexagon

DESCRIPTION

Neste Super Racing 2T low smoke and low ash fully synthetic top tier 2-stroke oil especially for motorcycles, mopeds, scooters chainsaws, snowmobiles, etc. used in very severe conditions.

The oil contains about 25 % solvent, which ensures a good oil-fuel mixture at sub zero temperatures.

FEATURES AND BENEFITS

- Excellent lubricity
- Excellent endurance at high temperatures
- Low smoke
- Less deposits

TYPICAL CHARACTERISTICS

Density 15 °C	875	kg/m ³	ASTM D4052
Flash Point (COC)	84	°C	ASTM D92
Pour Point	-48	°C	ASTM D5949
Sulfated Ash	0,17	w/w %	ASTM D874
Viscosity @ 100 °C	9,37	cSt	ASTM D445
Viscosity @ 40 °C	53,7	cSt	ASTM D445
Viscosity Index	159		ASTM D2270

APPLICATIONS

Neste Super Racing 2T is specially recommended for high performance air and water cooled 2T engines such as motorcycles, mopeds, scooters and chainsaws. Neste Super Racing 2T is also excellent in combination with alkylated gasoline.

For outboard engine use the recommendation is Neste Marine 2T. Neste Super Racing 2T is not necessarily suitable for Go-Kart racing. Please follow the engine manufacturers recommendations.

The oil is dyed blue so that it is possible to see if the fuel blend contains oil.