



Neste Pro F 5W-30

Synthetic motor oil

PERFORMANCE CLAIMS

API SL, SJ/CF

ACEA A5/B5, A1/B1

Fiat 9.55535.G1

Ford WSS-M2C913-A, B, C, D

Renault RN0700

DESCRIPTION

Neste Pro F 5W-30 is a fully synthetic high performance motor oil for extended oil drain intervals. Neste Pro F 5W-30 exceeds the performance criteria of API SL, SJ/CF and ACEA A5/B5 standards. It also exceeds original equipment manufacturer (OEM) requirements providing high performance in passenger car and van applications.

Neste Pro F 5W-30 is designed as a fuel economy oil which is achieved by low viscosity and improved friction modifiers.

It is possible to use Neste Pro F 5W-30 for long drain intervals as it is manufactured from high quality base oils with excellent anti-oxidative properties and Full SAPS technology with high TBN which will ensure outstanding engine cleanliness and wear protection during all drain intervals (always check drain interval range from your cars user manual).

It has very good temperature stability which enables easy cold start and effective engine protection at high temperatures.

FEATURES AND BENEFITS

- Excellent cold start performance
- Improved fuel economy benefits
- Long drain interval

TYPICAL CHARACTERISTICS

Viscosity (CCS) @ -30 °C	4200		
Density 15 °C	852	kg/m ³	ASTM D4052
Flash Point (COC)	222	°C	ASTM D92
Pour Point	-45	°C	ASTM D5949
Base Number (TBN)	10	mg KOH/g	ASTM D2896
Viscosity @ 100 °C	9,8	cSt	ASTM D445
Viscosity @ 40 °C	55	cSt	ASTM D445
Viscosity Index	166		ASTM D2270

APPLICATIONS

Neste Pro F 5W-30 is especially developed for Ford engines where Ford WSS-M2C913-C engine oil is required. It is also backwards compatible when Ford WSS-M2C913-B, M2C913-A or M2C912-A1 quality oil is specified. It is also suitable for Hyundai and KIA passenger cars and vans as well as for LPG motors.

Neste Pro F 5W-30 is recommended for gasoline and diesel motors which requires low friction and low viscosity oil.
