



Neste Gear UTTO

Hydraulic and driveline oil for agricultural equipment

PERFORMANCE CLAIMS

API GL-4

Allison C-4, C-3

Case MAT 3505

Ford M2C134-A, B, C, D

Ford M2C86-B, C

JDM J20A, B, C

JDM J14B, C

JDM J21A

Kubota UDT

MF M1135, M1141, M1143, M1145

Ford/New Holland FNHA-2-C-200.00 (hydraulic oil 134)

Ford/New Holland FNHA-2-C-201.00 (M2C-134D)

Versatile 23M, 24M

Volvo 97303 (VCE WB 101)

APPROVALS

ZF TE-ML 03E, 05F, 06D, 06K, 06N, 06R, 17E, 21F

DESCRIPTION

Neste Gear UTTO is a combined gear and hydraulic oil for tractors, with the friction properties required for wet brakes. Its wear resistance exceeds that of ordinary gear/hydraulic oils. Neste Gear UTTO also offers good oxidation and corrosion resistance.

FEATURES AND BENEFITS

- Good EP properties
- Multipurpose lubricant
- Very good wear protection

TYPICAL CHARACTERISTICS

Density 15 °C	874	kg/m ³	ASTM D4052
Flash Point (COC)	238	°C	ASTM D92
Pour Point	-42	°C	ASTM D5949
SAE equivalence	10W-30		
Viscosity @ 100 °C	10	cSt	ASTM D445
Viscosity @ 40 °C	67	cSt	ASTM D445
Viscosity Index	133		ASTM D2270

APPLICATIONS

Neste Gear UTTO oil is used in tractor gears, rear axles, hydraulics and wet brakes. Its viscosity is standard, and it is suitable for year-round use with the exception of severe below-zero colds.