



Neste Premium Gear UTTO

Synthetic hydraulic and driveline oil for agricultural equipment

PERFORMANCE CLAIMS

API GL-4

Case MS 1206

Case MS 1207

Case MS 1209

Caterpillar TO-2

Ford M2C86-A, B, C

Ford M2C134-C, D

JDM J20A, C

JDM J20B, D

MF M1110, M1127A, M1135, M1143

MF CMS M1145

New Holland NH-410B

Volvo 97303 (VCE WB 101)

DESCRIPTION

Neste Premium Gear UTTO is a combined gear and hydraulic oils for tractors, with the friction properties required for wet brakes. Its wear resistance exceeds that of ordinary gear/hydraulic oils. It also offers good oxidation and corrosion resistance.

FEATURES AND BENEFITS

- Good EP properties
- Multipurpose lubricant
- Very good wear protection
- Extra wide operating temperature area

TYPICAL CHARACTERISTICS

Viscosity (CCS) @ -20 °C	3000		
Density 15 °C	864	kg/m ³	ASTM D4052
Flash Point (COC)	226	°C	ASTM D92
Pour Point	-42	°C	ASTM D5949
SAE equivalence	5W-30		
Viscosity @ 100 °C	10,8	cSt	ASTM D445
Viscosity @ 40 °C	64	cSt	ASTM D445
Viscosity Index	160		ASTM D2270

APPLICATIONS

Neste Premium Gear UTTO is a synthetic quality suitable for an extremely wide range of temperatures. It works just as well in hot summer conditions as in a severe below-zero cold. Neste Premium Gear UTTO fills Caterpillar's hydraulic oil requirement min. 900ppm for zinc.