



Motor Oil 5W-40 Premium Synthetic C3

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Date of issue:

Revision date: 22/03/2016

Supersedes: 12/12/2013

version: 2.1

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixture
 Product name : Motor Oil 5W-40 Premium Synthetic C3
 Product code : 05000C3
 Product group : Blend

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1. Relevant identified uses

Main use category : Professional use, Industrial use, Consumer use
 Use of the substance/mixture : Automotive care products
 Function or use category : Lubricants and additives

1.2.2. Uses advised against

No additional information available

1.3. Details of the supplier of the safety data sheet

MPM International Oil Company
 Cyclotronweg 1
 2629 HN Delft - Nederland
 T +31 (0)15 2514030 - F +31 (0)15 2514031
info@mpmoil.nl - www.mpmoil.nl

1.4. Emergency telephone number

Emergency number : +31 (0)15 2514030 (08.00 - 17.00)

Country	Official advisory body	Address	Emergency number
Ireland	National Poisons Information Centre Beaumont Hospital	Beaumont Hospital Beaumont Road 9 Dublin	: +353 1 8379964
United Kingdom	Guy's & St Thomas' Poisons Unit Medical Toxicology Unit, Centre Hospitalier Universitaire de Constantine	Avonley Road SE14 5ER London	0870 243 2241

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Not classified

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

EUH-statements : EUH210 - Safety data sheet available on request
 EUH208 - Contains C14-16-18 Alkylphenol. May produce an allergic reaction

2.3. Other hazards

No additional information available

SECTION 3: Composition/information on ingredients

3.1. Substance

Not applicable

3.2. Mixture

Motor Oil 5W-40 Premium Synthetic C3

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based	(CAS No) 72623-87-1 (EC no) 276-738-4 (EC index no) 649-483-00-5 (REACH-no) 01-2119474889-13	40 - 50	Asp. Tox. 1, H304
Reaction products of benzeneamine, N-phenyl- with nonene (branched)	(CAS No) 36878-20-3 (EC no) 253-249-4 (REACH-no) 01-2119488911-28	1 - 2,49	Aquatic Chronic 4, H413
Zinc bis[O-(6-methylheptyl)] bis[O-(sec-butyl)] bis(dithiophosphate)	(EC no) 298-577-9 (EC index no) 272-028-3 (REACH-no) 01-21419543726-33	0,1 - 0,99	Skin Irrit. 2, H315 Eye Dam. 1, H318 Aquatic Chronic 2, H411
C14-16-18 Alkylphenol	(REACH-no) 01-2119498288-19	0,1 - 0,99	Skin Sens. 1, H317 Aquatic Chronic 4, H413

Full text of H-statements: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

General	: In case of accident or if you feel unwell, seek medical advice immediately (show safety data sheet if possible).
After inhalation	: Take victim to fresh air, in a quiet place and if necessary take medical advice.
After skin contact	: After contact with skin, take off immediately all contaminated clothing, and wash immediately with plenty of water and soap.
After eye contact	: Wash immediately with lots of water.
After ingestion	: If swallowed, do not induce vomiting: seek medical advice immediately and show this container label.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/injuries	: In case of accident or if you feel unwell, seek medical advice immediately (show this label if possible).
-------------------	---

4.3. Indication of any immediate medical attention and special treatment needed

First Aid, decontamination, treatment of symptoms.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media	: powder, alcohol-resistant foam, water spray, carbon dioxide.
Unsuitable extinguishing media	: Do not use a heavy water stream.

5.2. Special hazards arising from the substance or mixture

Fire hazard	: Although this substance has flammability data, it is difficult to ignite in air and is classified as non-flammable.
-------------	---

5.3. Advice for firefighters

Other information	: Use water spray/stream to protect personnel and to cool endangered containers.
-------------------	--

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures	: Keep away from sources of ignition - No smoking.
------------------	--

6.1.1. For non-emergency personnel

Protective equipment	: Wear suitable protective clothing and eye/face protection.
----------------------	--

6.1.2. For emergency responders

Protective equipment	: Wear respiratory protection. Wear suitable protective clothing and gloves.
----------------------	--

6.2. Environmental precautions

Avoid release to the environment. Prevent spreading over great surfaces (e.g. by damming or installing oil booms). Notify authorities if liquid enters sewers or public waters.

6.3. Methods and material for containment and cleaning up

For containment	: Prevent spreading over great surfaces (e.g. by damming or installing oil booms).
Methods for cleaning up	: Clean up with absorbent material (for example sand, sawdust, neutral absorbent granule, silica gel).
Other information	: Can be slippery on hard, smooth walking area.

Motor Oil 5W-40 Premium Synthetic C3

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

6.4. Reference to other sections

Information on disposal - see Section 13. Information on personal protective equipment - see Chapter 8. Information on safe handling - see Section 7.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Remove all sources of ignition.
Hygiene measures : When using do not eat, drink or smoke. Wash hands before breaks and at the end of work.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Provide for sufficient ventilation and punctiform suction at critical points.
Storage conditions : Store in original container.
Incompatible products : Do not use with strong oxidizing agents, nor with strong acids or strong bases.
Storage temperature : < 40 °C
Storage area : Ensure adequate ventilation of the storage area. Keep container tightly closed and dry.

7.3. Specific end use(s)

No additional information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Motor Oil 5W-40 Premium Synthetic C3		
EU	IOELV STEL (mg/m ³)	10 mg/m ³

Additional information : Based on ACGIH TLV, a concentration of 5 mg/m³ oilspray (TWA, 8 hour workday) is recommended.

8.2. Exposure controls

Technical measures : If suction of the immediate vicinity is impossible or insufficient, adequate airing of the working place must be ensured.
Personal protective equipment : Safety glasses.
Materials for protective clothing : Choosing the proper glove is a decision that depends not only on the type of material, but also on other quality features, which differ for each manufacturer. Suitable material: nitrile rubber, neoprene, PVC (Polyvinyl chloride)
Hand protection : Wear suitable gloves
Eye protection : Safety glasses
Skin and body protection : Wear suitable protective clothing
Respiratory protection : No personal breathing protective equipment is normally required



SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state : Liquid
Appearance : Oily.
Colour : brown.
Odour : characteristic.
Odour threshold : No data available
pH : No data available
Relative evaporation rate (butylacetate=1) : No data available
Melting point : No data available
Freezing point : No data available
Boiling point : No data available
Flash point : > 110 °C
Auto-ignition temperature : No data available
Decomposition temperature : No data available
Flammability (solid, gas) : No data available

Motor Oil 5W-40 Premium Synthetic C3

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Vapour pressure	: No data available
Relative vapour density at 20 °C	: No data available
Relative density	: No data available
Density	: 851 g/l 20C
Solubility	: Water: practically insoluble
Log Pow	: No data available
Viscosity, kinematic	: 84 mm ² /s 100C
Viscosity, dynamic	: No data available
Explosive properties	: No data available
Oxidising properties	: No data available
Explosive limits	: No data available

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

None under normal use.

10.2. Chemical stability

The product is stable at normal handling- and storage conditions.

10.3. Possibility of hazardous reactions

No additional information available

10.4. Conditions to avoid

None under normal use.

10.5. Incompatible materials

Oxidizing substances. Acids and bases.

10.6. Hazardous decomposition products

On burning: release of harmful/irritant gases/vapours e.g.: carbon monoxide - carbon dioxide.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity : Not classified

Zinc bis[O-(6-methylheptyl)] bis[O-(sec-butyl)] bis(dithiophosphate)	
LD50 oral rat	2600 mg/kg
LD50 dermal rat	> 3160 mg/kg OECD 402
Skin corrosion/irritation	: Not classified
Serious eye damage/irritation	: Not classified
Respiratory or skin sensitisation	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified
Reproductive toxicity	: Not classified
Specific target organ toxicity (single exposure)	: Not classified
Specific target organ toxicity (repeated exposure)	: Not classified
Aspiration hazard	: Not classified

Motor Oil 5W-40 Premium Synthetic C3	
Viscosity, kinematic	84 mm ² /s 100C

SECTION 12: Ecological information

12.1. Toxicity

Reaction products of benzeneamine, N-phenyl- with nonene (branched) (36878-20-3)	
LC50 fish 1	> 100 mg/l @ 96h
LC50 other aquatic organisms 1	600 mg/l @ 72h (Algae)
EC50 Daphnia 1	51 mg/l @ 48h
NOEC chronic algae	33 mg/l @ 96h

Motor Oil 5W-40 Premium Synthetic C3

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Zinc bis[O-(6-methylheptyl)] bis[O-(sec-butyl)] bis(dithiophosphate)	
LC50 fish 1	4,5 ml/l OECD 203 (Oncorhynchus mykiss) 96h
LC50 other aquatic organisms 1	2,1 ppm OECD 201 (Selenastrum capricornutum) 48h
EC50 Daphnia 1	5,4 ml/l OECD 202 (Daphnia magna) 48h

12.2. Persistence and degradability

Motor Oil 5W-40 Premium Synthetic C3	
Persistence and degradability	Not soluble in water, so only minimally biodegradable.
Reaction products of benzeneamine, N-phenyl- with nonene (branched) (36878-20-3)	
Persistence and degradability	Poorly biodegradable.
Biodegradation	0 % Sturm-test @28d
Zinc bis[O-(6-methylheptyl)] bis[O-(sec-butyl)] bis(dithiophosphate)	
Biodegradation	1,5 % OECD 301B 28d

12.3. Bioaccumulative potential

Reaction products of benzeneamine, N-phenyl- with nonene (branched) (36878-20-3)	
Bioconcentration factor (BCF REACH)	1730
Log Kow	3,6 @0.1d
Bioaccumulative potential	Moderate bioconcentration.
Zinc bis[O-(6-methylheptyl)] bis[O-(sec-butyl)] bis(dithiophosphate)	
Log Pow	0,9 @23C

12.4. Mobility in soil

Reaction products of benzeneamine, N-phenyl- with nonene (branched) (36878-20-3)	
Log Koc	> 2000
Soil	Low mobility (soil).

12.5. Results of PBT and vPvB assessment

Component	
Reaction products of benzeneamine, N-phenyl- with nonene (branched) (36878-20-3)	This substance does not meet the PBT/vPvB criteria of REACH, annex XIII.

12.6. Other adverse effects

No additional information available

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Regional legislation (waste)	: Waste disposal according to official state regulations.
Waste treatment methods	: Do not dispose of with domestic waste.
Waste materials	: After use, this oil must be sent to a used oil collecting location. Incorrect disposal of used oil endangers the environment. Every mixture with foreign substances such as solvents, brake- and cooling liquids is forbidden.
European List of Waste (LoW) code	: 13 02 00 - Waste engine, gear and lubricating oils. 13 02 05- Mineral-based non-chlorinated engine, gear and lubricating oils. 15 01 10 Packaging containing residues of or contaminated by dangerous substances

SECTION 14: Transport information

In accordance with ADR / RID / IMDG / IATA / ADN

14.1. UN number

Not regulated for transport

14.2. UN proper shipping name

Proper Shipping Name (ADR)	: Not applicable
Proper Shipping Name (IMDG)	: Not applicable

14.3. Transport hazard class(es)

ADR

Transport hazard class(es) (ADR) : Not applicable

IMDG

Transport hazard class(es) (IMDG) : Not applicable

Motor Oil 5W-40 Premium Synthetic C3

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

14.4. Packing group

Packing group (ADR) : Not applicable

Packing group (IMDG) : Not applicable

14.5. Environmental hazards

Dangerous for the environment : No

Marine pollutant : No

Other information : No supplementary information available

14.6. Special precautions for user

- Overland transport

No data available

- Transport by sea

No data available

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations

Contains no REACH substances with Annex XVII restrictions

Contains no substance on the REACH candidate list

Contains no REACH Annex XIV substances

15.1.2. National regulations

No additional information available

15.2. Chemical safety assessment

No additional information available

SECTION 16: Other information

Full text of H- and EUH-statements:

Aquatic Chronic 2	Hazardous to the aquatic environment — Chronic Hazard, Category 2
Aquatic Chronic 4	Hazardous to the aquatic environment — Chronic Hazard, Category 4
Asp. Tox. 1	Aspiration hazard, Category 1
Eye Dam. 1	Serious eye damage/eye irritation, Category 1
Skin Irrit. 2	Skin corrosion/irritation, Category 2
Skin Sens. 1	Sensitisation — Skin, Category 1
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H411	Toxic to aquatic life with long lasting effects.
H413	May cause long lasting harmful effects to aquatic life.
EUH208	Contains . May produce an allergic reaction.
EUH210	Safety data sheet available on request.

SDS MPM REACH

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product