



Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830 Revision date: 25/08/2014 Date of issue:

version: 27.0

1.1. Product identifier	
Product form	: Mixture
Product name	: Carburettor Cleaner Aerosol
Product code	: A101
Vaporizer	: Aerosol
1.2. Relevant identified use	s of the substance or mixture and uses advised against
1.2.1. Relevant identified use	S
Main use category	: Professional use
Use of the substance/mixture	: Automotive care products
1.2.2. Uses advised against	
No additional information available	
1.3. Details of the supplier	of the safety data sheet
MPM International Oil Company Cyclotronweg 1 2629 HN Delft - Nederland	

T +31 (0)15 2514030 - F +31 (0)15 2514031 info@mpmoil.nl - www.mpmoil.nl

Emergency telephone number 1.4.

Emergency number	: +31 (0)15 2514030 (08.00 - 17.00)				
Country	Official advisory body	Address	Emergency number		
Ireland National Poisons Information Centre Beaumont Hospital		Beaumont Hospital Beaumont Road 9 Dublin	: +353 1 8379964		
United Kingdom Guy's & St Thomas' Poisons Unit Medical Toxicology Unit, Centre Hospitalier Universitaire de Constantine		Avonley Road SE14 5ER London	0870 243 2241		

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Aerosol 1	H222;H229
Acute Tox. 4 (Inhalation)	H332
Skin Irrit. 2	H315
Eye Irrit. 2	H319
STOT SE 3	H336
STOT SE 3	H335
STOT RE 2	H373
Asp. Tox. 1	H304

Full text of hazard classes and H-statements : see section 16

2.2. Label elements

Labelling according to Regulation Hazard pictograms (CLP)	(EC) No. 1272/2008 [CLP]	
	GHS02 GHS07 GHS08	
CLP Signal word	: Danger.	
Hazardous ingredients	: xylene; Acetone	
Hazard statements (CLP)	: H222 - Extremely flammable aerosol H229 - Pressurised container: May burst if heated	
18/02/2016	EN (English)	1/8

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

	H315 - Causes skin irritation H319 - Causes serious eye irritation H332 - Harmful if inhaled H335 - May cause respiratory irritation H336 - May cause drowsiness or dizziness H373 - May cause damage to organs through prolonged or repeated exposure
Precautionary statements (CLP)	 P101 - If medical advice is needed, have product container or label at hand P102 - Keep out of reach of children P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking P211 - Do not spray on an open flame or other ignition source P251 - Do not pierce or burn, even after use P260 - Do not breathe gas, spray, vapours P271 - Use only outdoors or in a well-ventilated area P280 - Wear eye protection, face protection, protective gloves P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing P312 - Call a doctor, a POISON CENTER if you feel unwell P405 - Store locked up P410+P412 - Protect from sunlight. Do no expose to temperatures exceeding 50°C/ 122°F P501 - Dispose of contents/container to officially registered waste disposal company P300 - Without adequate ventilation formation of explosive mixtures may be possible

2.3. Other hazards

No additional information available

SECTION 3: Composition/information on ingredients

3.1. Substance

Not applicable

3.2. Mixture

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
xylene	(CAS No) 1330-20-7 (EC no) 215-535-7 (EC index no) 601-022-00-9	25 - 50	Flam. Liq. 3, H226 Acute Tox. 4 (Dermal), H312 Acute Tox. 4 (Inhalation:dust,mist), H332 Skin Irrit. 2, H315 Eye Irrit. 2, H319 STOT RE 2, H373 Asp. Tox. 1, H304
ethanol, ethyl alcohol	(CAS No) 64-17-5 (EC no) 200-578-6 (EC index no) 603-002-00-5	10 - 25	Flam. Liq. 2, H225
isobutane	(CAS No) 75-28-5 (EC no) 200-857-2 (EC index no) 601-004-00-0 (REACH-no) 01-2119485395-27	10 - 25	Flam. Gas 1, H220 Compressed gas, H280
Acetone	(CAS No) 67-64-1 (EC no) 200-662-2 (EC index no) 606-001-00-8	20 - 25	Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336
propane	(CAS No) 74-98-6 (EC no) 200-827-9 (EC index no) 601-003-00-5 (REACH-no) 01-2119486944-21	2,5 - 10	Flam. Gas 1, H220 Compressed gas, H280
butane	(CAS No) 106-97-8 (EC no) 203-448-7 (EC index no) 601-004-00-0 (REACH-no) 01-2119474691-32	1 - 2,5	Flam. Gas 1, H220 Compressed gas, H280
Distillates (petroleum), hydrotreated light naphthenic	(CAS No) 64742-53-6 (EC no) 265-156-6 (REACH-no) 01-2119480375-34	1 - 2,5	Asp. Tox. 1, H304

Full text of H-statements: see section 16

SECT	SECTION 4: First aid measures			
4.1.	Description of first aid measures			
General		: Symptoms of poisoning may develop several hours following exposure. Victim should be under medical observation for at least 48 hours after exposure.		

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

After inhalation	: Take victim to fresh air, in a quiet place and if necessary take medical advice. In case of unconsciousness place in unconscious position and seek medical advice.
After skin contact	 After contact with skin, take off immediately all contaminated clothing, and wash immediately with plenty of water and soap.
After eye contact	: In case of contact with eyes, rinse immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart. Subsequently consult an ophthalmologist.
After ingestion	: Do NOT induce vomiting. Get immediate medical advice/attention.
4.2. Most important symptoms and effe	cts, both acute and delayed
No additional information available	

4.3. Indication of any immediate medical attention and special treatment needed

No additional information available

SECTION 5: Firefighting measures		
5.1. Extinguishing media		
Suitable extinguishing media : Foam. Powder. Carbon dioxide (CO2).		
Unsuitable extinguishing media : Do not use a heavy water stream.		
5.2. Special hazards arising from the su	ubstance or mixture	
Fire hazard	: May form flammable/explosive vapour-air mixture. On heating/burning: release of (highly) toxic gases/vapours e.g.: carbon monoxide - carbon dioxide.	
Explosion hazard : Vapours may form explosive mixtures with air. Heat from a fire could result		
5.3. Advice for firefighters		
Protection during firefighting : Self-contained breathing apparatus with an air line.		
Other information	: Cool containers / tanks with spray water if possible. Do not allow water used to extinguish fire to enter drains or waterways.	

SECT	SECTION 6: Accidental release measures			
6.1.	1. Personal precautions, protective equipment and emergency procedures			
General	measures	:	Keep public away. Keep away from sources of ignition - No smoking.	
6.1.1.	For non-emergency personnel			
Protecti	ve equipment	:	Wear suitable protective clothing and eye/face protection. Wear respiratory protection.	
Emerge	ncy procedures	:	Provide adequate ventilation.	
6.1.2.	For emergency responders			
Protecti	ve equipment	:	Wear respiratory protection. Wear suitable protective clothing and eye/face protection.	
6.2.	Environmental precautions			
Notify a	uthorities if liquid enters sewers or public	wa	ters. Do not flush into surface water or sewer system. Avoid release to the environment.	
6.3.	Methods and material for containme	nt	and cleaning up	
For cont	ainment	:	Prevent spreading over great surfaces (e.g. by damming or installing oil booms).	
Methods	s for cleaning up	:	Clean up with absorbent material (for example sand, sawdust, neutral absorbent granule, silica gel).	
Other in	formation	:	Ensure adequate ventilation.	
6.4.	Reference to other sections			
Informa	tion on disposal - see Section 13.			
SECT	ON 7: Handling and storage			
7.1.	Precautions for safe handling			
Precaut	ions for safe handling	:	If suction of the immediate vicinity is impossible or insufficient, adequate airing of the working place must be ensured. Avoid contact with skin and eyes. Take precautionary measures against static discharge. Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50 °C. Do not pierce or burn, even after use. Do not spray on an open flame or other ignition source.	
I be and a second				

Hygiene measures	: when using do not eat, drink or smoke.
7.2. Conditions for safe storage, inc	luding any incompatibilities
Technical measures	: Store in a well-ventilated place. Keep container tightly closed.
Storage conditions	: Protect from heat and direct sunlight.
Prohibitions on mixed storage	: Observe official regulations on storing packagings with pressurized containers.
Storage area	: Keep container tightly closed in a cool, well-ventilated place. Store according to local legislation.

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

7.3. Specific end use(s)

No additional information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters				
xylene (1330-20-7)				
IOELV TWA (mg/m ³) 210 mg/m ³				
IOELV TWA (ppm)	50 ppm			
IOELV STEL (mg/m ³)	442 mg/m ³			
IOELV STEL (ppm) 100 ppm				
17-5)				
IOELV TWA (mg/m³)	260 (NL); 950 (NO); 960 (DE, CH, SK); 1000 (SE, CS, ET, LT, BG, LV, RU); 1900 (DK, FR, FI, GR, AT, HU, SL, HR, PL); 1907 (BE); 1910 (ES); 1920 (GB)			
IOELV TWA (ppm)	1000 (FR, GB, PT, BE, ES, DK, FI); 500 (DE, SE, NO, CH)			
IOELV STEL (mg/m ³)	1900 (LT, ET, NL, SE); 1920 (CH, SK); 2500 (FI); 3000 (CS); 3800 (AT); 9500 (FR)			
IOELV STEL (ppm)	5000 (FR); 1000 (SE, CH); 1300 (FI)			
butane (106-97-8)				
IOELV TWA (mg/m ³)	1430 mg/m ³			
IOELV TWA (ppm)	600 ppm			
	IOELV TWA (mg/m³) IOELV TWA (ppm) IOELV STEL (mg/m³) IOELV STEL (ppm) 17-5) IOELV TWA (mg/m³) IOELV TWA (ppm) IOELV STEL (mg/m³) IOELV STEL (mg/m³) IOELV STEL (ppm) IOELV STEL (mg/m³) IOELV STEL (ppm) IOELV STEL (ppm)			

8.2. Exposure controls

Personal protective equipment

Materials for protective clothing

Hand protection

Eye protection

Skin and body protection

Respiratory protection

Other information



: High gas/vapour concentration: gas mask with filter type AX. Gloves. Safety glasses.

- : Suitable material: Butyl rubber
- : In the cases of special applications, it is recommended to check the chemical resistance with the manufacturer of the gloves
- : Tightly sealed safety glasses
- : Wear suitable protective clothing
- : If technical suction or ventilation measures are not possible or are insufficient, protective breathing apparatus must be worn

: When using do not eat, drink or smoke. Wash hands before breaks and at the end of work. Do not breathe vapour or spray. Avoid contact with skin and eyes. Remove/Take off immediately all contaminated clothing.

SECTION 9: Physical and chemical properties		
9.1. Information on basic physical and chemical properties		
Physical state	: Gas	
Appearance	: Aerosol.	
Colour	: colourless.	
Odour	: aromatic.	
Odour threshold	: No data available	
pH	: No data available	
Relative evaporation rate (butylacetate=1)	: No data available	
Melting point	: Not determined.	
Freezing point	: Not determined.	
Boiling point	: < 0 °C Not determined.	
Flash point	: Not applicable as aerosol.	
Auto-ignition temperature	: > 200 °C	
Decomposition temperature	: No data available	
Flammability (solid, gas)	: No data available	
Vapour pressure	: No data available	

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Relative vapour density at 20 °C	: No data available
Relative density	: No data available
Density	: 742 g/l
Solubility	: Water: partially miscible Organic solvent:97,6 %
Log Pow	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
Explosive properties	: Product is not explosive. In use, may form flammable/explosive vapour-air mixture.
Oxidising properties	: No data available
Explosive limits	: No data available
9.2. Other information	
	· Deschust is not eveloping. Measure recurforms combasing with an

Other properties

: Product is not explosive. Vapours may form explosive mixtures with air.

SECTION	v 10: Stabilit	y and	reactiv	ity

10.1. Reactivity

No additional information available

10.2. Chemical stability

The product is stable at normal handling- and storage conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

Keep cool. Protect from sunlight. Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

10.5. Incompatible materials

No additional information available

10.6. Hazardous decomposition products

On burning: release of harmful/irritant gases/vapours e.g.: carbon monoxide - carbon dioxide.

SECTION 11: Toxicological information		
11.1. Information on toxicological effects		
Acute toxicity :	Inhalation: Harmful if inhaled.	
ATE CLP (gases)	4500,000 ppmv/4h	
ATE CLP (vapours)	11,000 mg/l/4h	
ATE CLP (dust,mist)	1,500 mg/l/4h	
xylene (1330-20-7)		
LD50 oral rat	4300 mg/kg	
LD50 dermal rabbit	2000 mg/kg	
LC50 inhalation rat (ppm)	21,7 mg/l/4h	
Acetone (67-64-1)		
LD50 oral rat	5800 mg/kg	
LD50 oral	20000 mg/kg	
LC50 inhalation rat (Vapours - mg/l/4h)	76 mg/l/4h	
ethanol, ethyl alcohol (64-17-5)		
LD50 oral rat	10470 mg/kg	
LD50 dermal rat	> 15800 mg/kg	
LC50 inhalation rat (mg/l)	30000 mg/m³ Air	
isobutane (75-28-5)		
LC50 inhalation rat (Vapours - mg/l/4h)	> 50 mg/l/4h	
propane (74-98-6)		
LC50 inhalation rat (Vapours - mg/l/4h)	20 mg/l/4h	
butane (106-97-8)		
LC50 inhalation rat (Vapours - mg/l/4h)	658 mg/l/4h	
Skin corrosion/irritation :	Causes skin irritation.	
Serious eye damage/irritation :	Causes serious eye irritation.	
Respiratory or skin sensitisation	Not classified	

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified
Reproductive toxicity	: Not classified
Specific target organ toxicity (single exposure)	: May cause drowsiness or dizziness. May cause respiratory irritation.
Specific target organ toxicity (repeated exposure)	: May cause damage to organs through prolonged or repeated exposure.
Aspiration hazard	: May be fatal if swallowed and enters airways.
Carburettor Cleaner Aerosol	
Vaporizer	Aerosol
Potential adverse human health effects and symptoms	: Irritating. May be narcotic.

SECTION 12: Ecological information		
12.1. Toxicity		
General	Do not release in groundwater, surfacewater or sewerage. Danger of drinking-water pollution (ground water).	
Ecology - water	Harmful to aquatic organisms.	
xylene (1330-20-7)		
EC50 Daphnia 1	165 mg/l	
ErC50 (other aquatic plants)	/48h 165 mg/l (daphnia)	
Acetone (67-64-1)		
EC50 Daphnia 1	88000 mg/l	
ethanol, ethyl alcohol (64-17-5)		
LC50 fish 1	11200 mg/l /96h	
EC50 Daphnia 1	5012 mg/l /48h Freshwater	
ErC50 (algae)	275 mg/l /72h Freshwater	

12.2. Persistence and degradability

No additional information available

12.3. Bioaccumulative potential	
No additional information available	
12.4. Mobility in soil	
No additional information available	
12.5. Results of PBT and vPvB asses	emont
No additional information available	Sment
12.6. Other adverse effects	
Other adverse effects	: Danger of drinking-water pollution (ground water).
SECTION 13: Disposal considera	tions
13.1. Waste treatment methods	
Waste treatment methods	: Do not dispose of with domestic waste.
Waste disposal recommendations	: Remove to an authorized waste treatment plant.
Waste materials	: Waste disposal according to official state regulations.
European List of Waste (LoW) code	: 15 01 04 - metallic packaging
	16 05 04* - gases in pressure containers (including halons) containing dangerous substances
SECTION 14: Transport informat	ion
In accordance with ADR / RID / IMDG / IATA	
14.1. UN number	
UN-No.	: 1950
UN-No. (IMDG)	: 1950
14.2. UN proper shipping name	

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

14.3. Transport hazard class(es)	
ADR	
Transport hazard class(es) (ADR)	: 2.1
Danger labels (UN)	: 2.1
IMDG	
Transport hazard class(es) (IMDG)	: 2.1
Danger labels (IMDG)	: 2.1
	•
14.4. Packing group	
Packing group (ADR)	: Not applicable
Packing group (IMDG)	: Not applicable
14.5. Environmental hazards	
Dangerous for the environment	: No
Marine pollutant	: No
Other information	: No supplementary information available
14.6. Special precautions for user	
- Overland transport	
Classification code (ADR)	: 5F
Limited quantities (ADR)	: 11
Transport category (ADR)	: 2
Tunnel restriction code (ADR)	: D
Transport by soa	
- Transport by sea	: SP277
Limited quantities (IMDG)	: 5P277 : F-D
EmS-No. (Fire) EmS-No. (Spillage)	: S-U
	nnex II of MARPOL 73/78 and the IBC Code
Not applicable	
SECTION 15: Regulatory informat	
15.1. Safety, health and environmenta	I regulations/legislation specific for the substance or mixture
15.1.1. EU-Regulations	
Contains no REACH substances with Annex	XVII restrictions
Contains no substance on the REACH candi	
Contains no REACH Annex XIV substances	
15.1.2. National regulations	
No additional information available	
15.2. Chemical safety assessment	
No additional information available	
SECTION 16: Other information	
SECTION 16: Other information	

Indication of changes:

18/02/2016

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

	Revision date	Modified	
	SDS EU format	Added	
	Vaporizer	Added	
	Type of product	Removed	
2.1	Classification according to Regulation (EC) No. 1272/2008 [CLP]	Modified	
2.2	Precautionary statements (CLP)	Modified	
2.2	Hazard statements (CLP)	Modified	
2.2	Hazard symbols	Modified	
2.2	R-phrases	Modified	
2.2	Hazard pictograms (CLP)	Modified	
3	Composition/informatio n on ingredients	Modified	
11.1	ATE CLP (dust,mist)	Added	
11.1	ATE CLP (vapours)	Added	
11.1	ATE CLP (gases)	Added	

Full text of H- and EUH-statements:	
Acute Tox. 4 (Dermal)	Acute toxicity (dermal), Category 4
Acute Tox. 4 (Inhalation)	Acute toxicity (inhal.), Category 4
Acute Tox. 4 (Inhalation:dust,mist)	Acute toxicity (inhalation:dust,mist) Category 4
Aerosol 1	Aerosol, Category 1
Asp. Tox. 1	Aspiration hazard, Category 1
Compressed gas	Gases under pressure : Compressed gas
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2
Flam. Gas 1	Flammable gases, Category 1
Flam. Liq. 2	Flammable liquids, Category 2
Flam. Liq. 3	Flammable liquids, Category 3
Skin Irrit. 2	Skin corrosion/irritation, Category 2
STOT RE 2	Specific target organ toxicity — Repeated exposure, Category 2
STOT SE 3	Specific target organ toxicity — Single exposure, Category 3, Narcosis
STOT SE 3	Specific target organ toxicity — Single exposure, Category 3, Respiratory tract irritation
H220	Extremely flammable gas.
H222	Extremely flammable aerosol
H225	Highly flammable liquid and vapour
H226	Flammable liquid and vapour
H229	Pressurised container: May burst if heated.
H280	Contains gas under pressure; may explode if heated
H304	May be fatal if swallowed and enters airways.
H312	Harmful in contact with skin.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H335	May cause respiratory irritation
H336	May cause drowsiness or dizziness.
H373	May cause damage to organs through prolonged or repeated exposure.

SDS MPM REACH

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product